



DUMP TRAILERS

www.bigtextrailers.com

25DU

Complete Break-A-Way System with Charge Line

Spare Tire Mount

Double 1/2" Tie Rods on all Sides

48" Sides with Formed Channel Supports

4-5/8" D-Rings Inside Bed

Removable Header Across Rear

Double Rear Gates with Cam Latch

Heavy Duty 10 Gauge Floor

Rubber Mounted Sealed LED Lighting

Self Contained Electric Hydraulic Scissor Lift

Dual 16" Tires (8 bolt)

Lockable Control Unit

Safety Chains Attached w/ Cold Rolled Eyelets

Fully Enclosed Pump & Battery Box

- Tandem Dual Gooseneck Dump Available in 92" Width and in Lengths of 18' and 20'
- Approximate Payload Ranges from 17,300# to 17,800#, Depending on Lengths
- Box Capacity of 21.98 Cubic Yards for the 18' Length
- Box Capacity of 23.70 Cubic Yards for the 20' Length

70SR



- Tandem Axle Single Ram Dump Available in 60" x 10'
- 2-5/16" Stamped A-Frame Coupler
- Approximate Payload of 5,100#
- Box Capacity of 3 Cubic Yards for the 5' Wide
- 15" Tires (5 bolt)
- 20", 16 Gauge Sides with Formed Channel Supports
- Enclosed Pump and Battery Box
- 16 Gauge Floor
- Lockable Control Unit
- Single Cylinder Lift
- J-Hooks on All Sides
- Tarp Brackets
- 1 Piece 2-Way Style Rear Gate

10SR



- 83" x 12' Low Profile Tandem Axle Dump
- 2-5/16" Adjustable Forged Coupler
- Approximate Payload of 6,600#
- Box Capacity of 6.2 Cubic Yards
- 16" Tires (6 bolt)
- 24", 12 Gauge Sides
- Enclosed Pump and Battery Box
- 10 Gauge Floor
- Modular Sealed Wiring Harness
- Self Contained Electric/Hydraulic Single Cylinder Lift
- 1/2" Tie Rail on All Four Sides
- Stake Pockets on Sides and Front
- Tarp Brackets
- Combo Gate
- Available in Black Only

10LX



- 83" x 12' Tandem Axle Low Profile Extra Wide Dump
- 2-5/16" Adjustable Forged Coupler
- Approximate Payload of 6,270#
- Box Capacity of 6.2 Cubic Yards
- 16" Tires (8 bolt)
- 24", 12 Gauge Sides with Formed Channel Supports
- Enclosed Pump & Battery Box
- 10 Gauge Floor
- Lockable Control Unit
- Self Contained Electric/Hydraulic Scissor Lift
- Tarp Brackets
- 1/2" Tie Rail on All Sides
- Stake Pockets (sides & front)
- Four 5/8" D-Rings Inside Bed
- Double Rear Gates with Cam Latch

12LX



- 83" x 12' Tandem Axle Low Profile Extra Wide Dump
- 2-5/16" Adjustable Forged Coupler
- Approximate Payload of 8,300#
- Box Capacity of 6.2 Cubic Yards
- 16" Tires (8 bolt)
- 24", 12 Gauge Sides with Formed Channel Supports
- Enclosed Pump & Battery Box
- 10 Gauge Floor
- Lockable Control Unit
- Self Contained Electric/Hydraulic Scissor Lift
- Tarp Brackets
- 1/2" Tie Rail on All Sides
- Stake Pockets (sides & front)
- Four 5/8" D-Rings Inside Bed
- Double Rear Gates with Cam Latch

14LX



*Shown with tarp option

- Tandem Axle Low Profile Extra Wide Bumper Pull Dump
- 83" Wide and in Lengths of 14' and 16'
- 2-5/16" Adjustable Forged Coupler
- Approximate Payload is 9,500# to 9,800#
- Box Capacity ranges from 7.2 Cubic Yards to 8.3 Cubic Yards
- 16" Tires (8 bolt)
- 24" High, 12 Gauge Sides with Formed Channel Supports
- Enclosed Pump & Battery Box
- 10 Gauge Floor
- Lockable Control Unit
- Fully Self Contained Electric/Hydraulic Scissor Lift
- 1/2" Tie Rail on All Sides
- Stake Pockets (sides & front)
- Tarp Brackets
- Four 5/8" D-Rings Inside Bed
- Double Rear Gates with Cam Latch

14GX



- Tandem Axle Low Profile Extra Wide Gooseneck Dump
- 83" Wide and in Lengths of 14' and 16'
- 2-5/16" Adjustable Pipe Coupler
- Approximate Payload is 8,700# to 9,000#
- Box Capacity ranges from 7.2 Cubic Yards to 8.3 Cubic Yards
- 16" Tires (8 bolt)
- 24", 12 Gauge Sides with Formed Channel Supports
- Enclosed Pump & Battery Box
- 10 Gauge Floor
- Lockable Control Unit
- Fully Self Contained Electric/Hydraulic Scissor Lift
- 1/2" Tie Rail on All Sides
- Stake Pockets (sides & front)
- Tarp Brackets
- Four 5/8" D-Rings Inside Bed
- Double Rear Gates with Cam Latch

140D



- 96" x 14' Tandem Over The Axle Bumper Pull Dump
- 2-5/16" Adjustable Forged Coupler
- Approximate Payload is 9,800#
- Box Capacity of 6.2 Cubic Yards
- 16" Tires (8 bolt)
- 18", 10 Gauge Fold Down Sides
- Enclosed Pump & Battery Box
- 10 Gauge Floor
- Lockable Control Unit
- Fully Self Contained Electric/Hydraulic Scissor Lift
- Tarp Brackets
- Four 5/8" D-Rings Inside Bed
- Combo Gate
- 7' Slide In Ramps

140D-GN



- 96" x 14' Tandem Over The Axle Gooseneck Dump
- 2-5/16" Adjustable Pipe Coupler
- Approximate Payload is 8,800#
- Box Capacity of 6.2 Cubic Yards
- 16" Tires (8 bolt)
- 18", 10 Gauge Fold Down Sides
- Enclosed Pump & Battery Box
- 10 Gauge Floor
- Lockable Control Unit
- Fully Self Contained Electric/Hydraulic Scissor Lift
- Tarp Brackets
- Four 5/8" D-Rings Inside Bed
- Combo Gate
- 7' Slide In Ramps

21GX



- 83" x 16' Triple Axle Low Profile Extra Wide Dump
- 2-5/16" Adjustable Pipe Coupler
- Approximate Payload of 14,800#
- Box Capacity of 8.3 Cubic Yards
- 16" Tires (8 bolt)
- 24", 12 Gauge Sides with Formed Channel Supports
- Enclosed Pump & Battery Box
- 10 Gauge Floor
- Lockable Control Unit
- Self Contained Electric/Hydraulic Scissor Lift
- 1/2" Tie Rail on All Sides
- Stake Pockets (sides & front)
- Tarp Brackets
- Four 5/8" D-Rings Inside Bed
- Double Rear Doors

APPROXIMATE WEIGHTS OF COMMON AGGREGATES PER CUBIC YARD

