

STANDARD FEATURES

AVAILABLE SIZES

8'-6" length 9'-4" length

11'-4" length

DESIGN FEATURES & HARDWARE

All steel frame construction

4" steel channel frame rails

3" steel channel cross members

1/8" steel tread plate deck

Steel tubing headache rack with round "easy view" window grill

Side rub rails with stake pockets

Angled Fuel Fill

Removable 4" tall side rails

Two lockable flush mounted tool boxes with paddle handle rotary latches, one per side, located in

front of wheel well

Recessed gooseneck ball mounting box with easy access removable cover and two safety chain loops Rear bumper with aluminum tread plate trim

Full access receiver mount

Full length rear skirt

Full length side skirt with rolled fenders and aluminum tread plate trim

Rear bed corners tapered for turning radius Premium TGIC Polyester powdercoating: black

LIGHTS

Two recessed tail, brake, and back up lights mounted in headache rack

Stop, turn, tail, back up, and tag lights in skirt DOT required lighting (clearance and marker lights) All lighting must be wired to meet all DOT requirements as originally intended by the vehicle manufacturer

FENDER WELLS

Due to various chassis lengths and configurations, specific measurements may determine the fender well placement on skirted beds (i.e. 2003 Dodge is 58" cab to axle measurement, whereas Ford and Chevy are 56" on bed off models)

POPULAR OPTIONS




Tool Box



60" Tall Headache Rack



Permanent Round Rails



Dovetail



Gooseneck Trough



- 1. Recessed back up lights mounted in headache rack
- 2. Round "easy view" window grill
- 3. Premium TGIC Polyester powdercoating: black
- Recessed gooseneck ball mounting box with easy access removable cover
- 5. Pull up safety chain loops
- 6. Durable 1/8" steel tread plate deck with 3" steel channel cross members and 4" steel channel frame rails
- 7. Rear bumper with aluminum tread plate trim

- 8. Bed corners tapered for turning radius
- 9. 7-way and 4-way trailer light plug installed
- 10. Lighted recessed tag compartment
- 11. DOT required lighting

Model may show options

- 12. Class IV 10 K receiver mount and two flush mounted safety chain catch points
- 13. New style bumper reinforcement





- 14. Side rub rails with stake pockets and removable 4" tall side rails
- 15. Two lockable flush mounted tool boxes with paddle handle rotary latches, one per side, located in front of wheel well
- 16. Full length side and rear skirt with rolled fenders and aluminum tread plate trim
- 17. Seam sealed rear corner

